

14 Cubic foot bucket with a 2,100 lb payload capacity

Tie down rings to secure on a trailer

Engine cover fully encloses the engine components

Rubber tracks for extra load capacity and traction

Narrow 33.3" width allows buggy to fit through 36" doors



**3 gal (11.35 L)
FUEL
CAPACITY**



**HONDA GX630
(688 cc)
GASOLINE
WITH ELECTRIC
STARTER**



**20 hp (15 kW)
HORSEPOWER
WITH TOP SPEED OF
WORK: 4 mph (6 kph)
TRAVEL: 6 mph (10 kph)**



**98.4 x 31.5 x 54 in
(250 x 84.5 x 137.1 cm)
DIMENSIONS
(L X W X H)**

AT14S

The AT14S rubber track concrete buggy delivers excellent performance and precise maneuverability. Equipped with a 90-degree dump angle and 180-degree pivoting dump, this buggy can place your material exactly where you need it.



Scan this QR code to learn more details about this product.



SPECIFICATIONS

SPECIFICATIONS	AT14S
ENGINE	HONDA GX630 (688 cc)
HORSEPOWER CLASS	20 hp (15 kW)
STARTER	Electric
FUEL TYPE	Gasoline
FUEL CAPACITY	3 gal (11.35 L)
TOP SPEED	WORK: 4 mph (6 kph) TRAVEL: 6 mph (10 kph)
PAYLOAD	1,785 lb (810 kg)
BUCKET CAPACITY	14 cu. ft. (0.39 m ³)
DUMP ANGLE	90°
DUMP / RETURN SPEED EMPTY	8 Seconds
PIVOT ANGLE	180°
WEIGHT	1,540 lb (699 kg)
DIMENSIONS (L X W X H)	98.4 x 31.5 x 54 in (250 x 84.5 x 137.1 cm)

PART NO.	MODEL NO.	DESCRIPTION
073370	AT14PBESD	14 cu. ft., Poly Bucket, Swivel Dump, Gas, Electric Start

