

 $(L \times W \times H)$



details about this product.

AW16-H

Wheel Buggy comes equipped with a Honda electric or recoil starter, a fuel capacity of 1.7 gallons, a top speed of seven miles per hour, and a sixteen cubic foot bucket, and foam filled tires. This wheel buggy was engineered with an all-steel frame to perform on the most demanding job sites.

SPECIFICATIONS

SPECIFICATIONS	AW16-H
ENGINE	HONDA GX390
HORSEPOWER CLASS	13 hp (9.6 kW)
STARTER	Recoil or Electric
FUEL TYPE	Gasoline
FUEL CAPACITY	1.7 gal (6 L)
TOP SPEED	7 mph (11.2 kph)
PAYLOAD	2,500 lbs (1134 kg)
BUCKET CAPACITY	16 cu. ft. (0.45 m³)
LIFT CYLINDER DIAMETER	2 in (51 mm)
DUMP ANGLE	90°
DUMP / RETURN SPEED EMPTY	5 Seconds
WHEELBASE	40 in (102 cm)
TIRES	Foam Filled
WEIGHT	1,365 lb (619 kg) or 1,375 lb (624 kg)
DIMENSIONS (L x W x H)	97 x 47 x 50 in (246 x 119 x 127 cm)

PART NO.	MODEL NO.	DESCRIPTION
058801	AW16-HR	16 cu. ft., Gas, Recoil Start
058802	AW16-HE	16 cu. ft., Gas, Electric Start

