

Fine pitch handles use a twist action to control blade pitch from flat to 28° and anything in between.

Rapid pitch handles use a ratcheting action to provide easy adjustment with the push or pull of a lever.

SPECIFICATIONS

SPECIFICATION	NS	PRO446TC
ENGINE		Honda GX390 (389 cc)
HORSEPOWER CLASS		13 hp (9.7 kW)
FUEL TYPE		Gasoline
ROTOR DIAMETER		46 in (117 cm) 4-Blades
MAXIMUM ROTOR SPEED		180 rpm
TROWEL ARMS & SPIDER		Super Duty
WEIGHT		315 lb (143 kg)
DIMENSIONS (L X W X H)		78 x 48 x 39 in (198.1 x 121.9 x 99.1 cm)
PART NO.	MODEL NO.	DESCRIPTION
055904A	TWPC44613F	PRO446TC - 13 hp class engine, torque convertor clutch, fine pitch handle, stationary guard ring, heavy-duty trowel arms, lift hook
058899A	TWPC44613P	PRO446TC - 13 hp class engine, torque convertor clutch, rapid pitch handle, stationary guard ring, heavy-duty trowel arms, lift hook
PART NO.	MODEL NO.	HANDLE OPTIONS
063975	TWPHF-L	Fine pitch handle w/ carry bar & handle pad for PRO Walkers, 33 lb (15 kg)
070300	TWPHR-L	Rapid pitch handle w/ carry bar & handle pad for PRO Walkers, 33 lb (15 kg)

BLADE & PAN RECOMMENDATIONS

BLADES	PRO446TC
FINISH	015695V-4: 6" x 18", Finish - Silver Series
FLAT FINISH	028489V-4: 8" x 18", Flat Finish - Silver Series
СОМВО	016094V-4: 8" x 18", Combo - Silver Series COMES WITH THESE BLADES
CLIP ON FLOAT (RH)	02822618V-4: 10" x 18", Clip-On Float - Silver Series
PLASTIC FINISH	047230-4: 6" x 18", Finish - Poly / Steel Backed
PANS	PRO446TC
CLIP-ON DISHED	051554 - 46.5" O.D. 80° Lip Angle





Fine pitch handles use a twist action to control blade pitch from flat to 28° and anything in between.



Rapid pitch handles use a ratcheting action to provide easy adjustment with the push or pull of a lever.