



Scan this QR code to learn more details about this product.



The centrally located grease port allows for ease of maintenance.



5-BLADED

SPIDER

The spray button has been relocated to the foot pedal for contractor convenience.

mind. The new MSP465 comes equipped with assisted steering, reducing operator fatigue. It comes with a powerful 57 hp Kubota liquidcooled gasoline engine that keeps this machine running cooler, and a 10-gallon fuel tank for longer run times. This rider produces excellent torque even at high rotor speeds, which makes it excellent for panning or finishing operations.

## **SPECIFICATIONS**

SPECIFICATIONS	MSP465
ENGINE	Kubota WG1605
HORSEPOWER CLASS	57 hp (43 kW)
FUEL TYPE	Liquid-Cooled Gasoline
PANNING PATH WIDTH	101 in (257 cm)   8' Class
ROTOR DIAMETER	45.7 in (116 cm) 5-Bladed Spider
MAXIMUM ROTOR SPEED	170 rpm
STEERING CONTROL SYSTEM	Power
FUEL CAPACITY	10 gal (37.9 L)
RETARDANT CAPACITY	6 gal (23 L)
WEIGHT	1,579 lb ( kg)
DIMENSIONS (L X W X H)	101.6 x 50.5 x 60.3 in (258.1 x 128.3 x 153.2 cm)

PART NO.	MODEL NO.	DESCRIPTION
074200	TR-MSP465	Mechanical "TC" Torque Converter Clutch Drive, Manual Steering, Super HD Gearboxes, Twin 46" (117 cm) 5-blade rotors, Kubota WG1605 gas 57 hp class engine, 4 lights, power retardant spray, 45-170 RPM Rotor Speeds
PART NO.	MODEL NO.	OPTIONAL ACCESSORIES
PART NO. 039090	MODEL NO. TR-DJMSP	OPTIONAL ACCESSORIES  Dolly Jacks, Pneumatic Tires, Set of two, 121 lb (55 kg)

## **BLADE & PAN RECOMMENDATIONS**

BLADES		MSP465
TYPE	PART NO.	DESCRIPTION
FINISH	015695AV-4	6" x 18" Finish - Silver Series
FLAT FINISH	028489V-4	8" x 18" Flat Finish - Silver Series, <b>COMES WITH THE MACHINE</b>
COMBO	016094AV-4	8" x 18" Combo - Blue Series
CLIP-ON FLOAT (LH)	02822318V-4	10" x 18" Clip-On - Left Hand - Silver Series
CLIP-ON FLOAT (RH)	02822618V-4	10" x 18" Clip-On - Right Hand - Silver Series
PLASTIC FINISH	047230-4	6" x 18" - Finish - Poly / Steel Backed
PANS		MSP465
TYPE	PART NO.	DESCRIPTION
CLIP-ON DISHED	051561	46.5" O.D 45° Lip Angle - 5-Blade
SAFETY CATCH DISHED	051562	46.5" O.D 45° Lip Angle - 5-Blade
CLIP ON FLAT	051552	46.5" O.D 80° Lip Angle - 5-Blade
SAFETY CATCH FLAT	051553	46.5" O.D 80° Lip Angle - 5-Blade