PLACING

BUGGIES: TRACK BUGGIES





Scan this QR code to learn more details about this product.

101 x 38.5 x 52 in (257 x 98 x 132.1 cm) DIMENSIONS (L X W X H)



track buggy. Designed for professional contractors, this reliable equipment boasts precise maneuvering capabilities and topnotch performance. The sturdy steel bucket with a 90-degree dump angle and 180-degree pivoting dump ensures accurate material placement, allowing you to achieve superior results every time.

SPECIFICATIONS

SPECIFICATIONS	AT19S
ENGINE	Kubota D902 (898 cc)
HORSEPOWER CLASS	21 hp (16 kW)
STARTER	Electric
FUEL TYPE	Diesel
FUEL CAPACITY	4 gal (15.14 L)
TOP SPEED	WORK: 4 mph (6 kph) TRAVEL: 6 mph (10 kph)
PAYLOAD	2,900 lb (953 kg)
BUCKET CAPACITY	19 cu. ft. (0.54 m3)
DUMP ANGLE	90°
DUMP / RETURN SPEED EMPTY	8 Seconds
PIVOT ANGLE	180°
WEIGHT	2,180 lb (990 kg)
DIMENSIONS (L X W X H)	101 x 38.5 x 52 in (257 x 98 x 132.1 cm)

PART NO.	MODEL NO.	DESCRIPTION
076000	AT19PBESD	19 cu. ft., Steel Bucket, Swivel Dump, Gas, Electric Start

