

PLACING

BUGGIES: TRACK BUGGIES



**1.72 gal
(6.5 L)
FUEL
CAPACITY**



**B&S VANGUARD
(627 cc)
GASOLINE
WITH ELECTRIC
STARTER**



**23 hp (17.2 kW)
HORSEPOWER
WITH TOP SPEED OF
WORK: 2.6 mph (4.2 kph)
TRAVEL: 5.5 mph (8.8 kph)**



**97 x 31 x 51.5 in
(246 x 79 x 131 cm)
DIMENSIONS
(L X W X H)**

15 Cubic foot bucket
with a 2,450 lb
payload capacity

Poly bucket design
allows bucket to be
cleaned more efficiently

Hydraulic
brake
system

Engine
cover fully
encloses
the engine
components

Narrow 31.5" width allows buggy to
fit through 36" doors

Tie down
rings to
secure on a
trailer

Rubber tracks
for extra load
capacity and
traction

AT15F

The AT15F rubber track buggy stands as a robust and agile workhorse, perfectly suited for transporting and offloading various bulk materials. Fitted with user-friendly controls, a powerful 23 hp engine, and a capacious 15 cubic foot poly bucket, this machine is an ideal choice for concrete professionals, landscaping experts, contractors, or anyone with frequent material hauling and dumping needs.



SPECIFICATIONS

SPECIFICATIONS	AT15F
ENGINE	B&S Vanguard (627 cc)
HORSEPOWER CLASS	23 hp (17.2 kW)
STARTER	Electric
FUEL TYPE	Gasoline
FUEL CAPACITY	1.72 gal (6.5 L)
TOP SPEED	WORK: 2.6 mph (4.2 kph) TRAVEL: 5.5 mph (8.8 kph)
PAYLOAD	2,450 lb (1200 kg)
BUCKET CAPACITY	15 cu. ft. (0.42 m ³)
DUMP ANGLE	90°
DUMP / RETURN SPEED EMPTY	4 Seconds
PIVOT ANGLE	180°
WEIGHT	1,650 lb (750 kg)
DIMENSIONS (L X W X H)	97 x 31 x 51.5 in (246 x 79 x 131 cm)

PART NO.	MODEL NO.	DESCRIPTION
079369	AT15FPBEP	15 cu. ft., Poly Bucket, Fixed Dump, Gas, Electric Start

