



3 gal (11.35 L)  
FUEL  
CAPACITY



HONDA GX630  
(688 cc)  
GASOLINE  
WITH ELECTRIC  
STARTER



20 hp (15 kW)  
HORSEPOWER  
WITH TOP SPEED OF  
WORK: 4 mph (6 kph)  
TRAVEL: 6 mph (10 kph)



98.4 x 31.5 x 54 in  
(250 x 84.5 x 137.1 cm)  
DIMENSIONS  
(L X W X H)

14 Cubic foot bucket with a  
2,100 lb payload capacity

Tie down rings  
to secure on a  
trailer

Narrow 33.3" width allows  
buggy to fit through 36"  
doors

Rubber tracks for extra  
load capacity and  
traction

Engine cover  
fully encloses  
the engine  
components



## AT14S

The AT14S rubber track concrete buggy delivers excellent performance and precise maneuverability. Equipped with a 90-degree dump angle and 180-degree pivoting dump, this buggy can place your material exactly where you need it.



Scan this QR code to learn more details about this product.



## SPECIFICATIONS

SPECIFICATIONS	AT14S
ENGINE	HONDA GX630 (688 cc)
HORSEPOWER CLASS	20 hp (15 kW)
STARTER	Electric
FUEL TYPE	Gasoline
FUEL CAPACITY	3 gal (11.35 L)
TOP SPEED	WORK: 4 mph (6 kph) TRAVEL: 6 mph (10 kph)
PAYLOAD	1,785 lb (810 kg)
BUCKET CAPACITY	14 cu. ft. (0.39 m <sup>3</sup> )
DUMP ANGLE	90°
DUMP / RETURN SPEED EMPTY	8 Seconds
PIVOT ANGLE	180°
WEIGHT	1,540 lb (699 kg)
DIMENSIONS (L X W X H)	98.4 x 31.5 x 54 in (250 x 84.5 x 137.1 cm)

PART NO.	MODEL NO.	DESCRIPTION
073370	AT14PBESD	14 cu. ft., Poly Bucket, Swivel Dump, Gas, Electric Start

