

SLABTONIC

CONCRETE FINISHING SOLUTION

SLABTONIC is a low VOC, non-film forming finishing aid and evaporation retardant designed to improve concrete workability during floating and troweling. It helps slow moisture loss, extend finishing time, and produce smoother, more consistent slab finishes in challenging conditions like heat, wind, and low humidity.

The colloidal silica formula lubricates the surface, increases cream, and makes finishing easier while improving surface consolidation, durability, abrasion resistance, and reducing the potential for checking, crazing, dusting, stains, and efflorescence.

BUILT FOR TOUGH CONDITIONS

- ✓ Interior & exterior applications
- ✓ Low VOC, non-film forming formula
- ✓ Ideal for hot, windy, and dry environments
- ✓ Type 1L cement

BEFORE

AFTER



BETTER SURFACE QUALITY

- ✓ Increases cream for smoother finishing
- ✓ Improves slab consolidation
- ✓ Helps reduce checking and crazing
- ✓ Minimizes dusting and efflorescence

EASIER FINISHING

- ✓ Extends concrete workability
- ✓ Slows rapid surface evaporation
- ✓ Makes floating and troweling easier
- ✓ Improves finishing consistency

SLABTONIC

CONCRETE FINISHING SOLUTION



APPLICATION FOR BEST RESULTS

- 1 Apply first coat immediately after screeding and before bull floating.
- 2 Apply second coat before first panning.
- 3 Apply third coat before second panning.

APPLICATION NOTES

- Apply using a high-volume, low-pressure sprayer.
- Spray as a fine, uniform mist.
- Product is ready to use.
- Mild agitation recommended before use.
- Do not over apply.



COVERAGE

Apply at a rate of

1,200 SQ. FT.
PER GALLON
PER APPLICATION



TECHNICAL DATA

PROPERTY	VALUE
Appearance	Clear Liquid
Odor	slight Odor
VOC Content	< 50 g/l
pH Level	10.5 - 11.5
Evaporation Rate	> 1.0
Vapor Pressure	> 2.2 torr @ 68°F (20°C)
Vapor Density (air = 1)	> 1
Drying Time @ 70°F, 77% RH	Approx. 1 Hour
Foot Traffic	Approx. 1 Hour
Wheel Traffic	6 - 10 Hours



PACKAGING

ITEM	PACKAGE	GALLONS	LITERS
082179	Bucket	5	18.93



STORAGE INFORMATION

- Do not break seal until product is ready for use.
- Do not allow product to freeze.
- Store in a well ventilated, cool, dry location.
- Maintain temperatures between 40°F – 100°F (4°C – 38°C).
- Shelf life is 24 months in its original unopened container.



SPECIFICATIONS / COMPLIANCE

- ASTM E96-10
- ASTM C944
- ASTM C797
- ASTM C1583
- USDA Compliant
- FDA Approved



IMPORTANT NOTES

- Slab Tonic is designed to be floated or troweled into the concrete surface.
- Do not blend or mix with other products.
- Over application may retard set time of the concrete.
- Consult SDS before use.
- Incompatible with strong oxidizers and strong acids.



WARNING

Irritant. Avoid contact with eyes and skin. Keep out of reach of children. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash thoroughly. Do not ingest. Read label and SDS before use.